AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1-12. (cancelled)

13. (currently amended) A decorative band intended for completely surrounding the <u>a</u> periphery of a food packaging, the decorative band comprising:

a lateral annular wall extending between a bottom and an upper face, the band extending longitudinally between two ends, and having a first and a second longitudinal edge;

at least one first portion extending longitudinally, having a maximum width L1; and

at least one second portion having a minimum width L2, the minimum width L2 being between one third and two thirds of the maximum width L1,

wherein the lateral annular wall, the at least one first portion, and the at least one second portion are formed of a film material, and configured to completely surround said periphery of said food packaging, and

wherein the first edge is rectilinear and substantially parallel to a longitudinal axis of the band.

- 14. (previously presented) The band as claimed in claim 13, wherein the second edge has a convex profile along the first portion and a concave profile along the second portion, the convex profile being complementary to the concave profile.
- 15. (currently amended) The band as claimed in either claim 13, wherein the second edge has a profile of a continuous wavy an undulating line, the line extending in a first direction and undulating in a second direction perpendicular to the first direction.
- 16. (previously presented) The band as claimed in claim 13, wherein the maximum width L1 is substantially equal to a maximum height H of the lateral wall of the food packaging.
- 17. (withdrawn) A strip of film material comprising printed designs, wherein the printed designs define, in a direction of a width of the strip, a contour of an even number of rows of bands, each band extending longitudinally between two ends and having a first and a second longitudinal edge, and having at least one first portion extending longitudinally and having a maximum width L1, and at least one second portion having a minimum width L2, the minimum width L2 being between one third and two thirds of the maximum width L1, and the first longitudinal edge being rectilinear and substantially parallel to

Docket No. 0600-1059 Appln. No. 10/577,724

a longitudinal axis of the band,

wherein the second edge has a convex profile along the first portion and a concave profile along the second portion, the convex profile being complementary to the concave profile, and

wherein the bands are arranged such that the second edges of the bands of two successive rows are adjacent, and such that the first edge of the first row and the first edge of the last row are contiguous to longitudinal edges of the strip.

18. (withdrawn) A food packaging having a lateral annular wall extending between a bottom and an upper face, wherein a periphery of the lateral wall is surrounded by a decorative band,

the band extending longitudinally between two ends and having a first and a second longitudinal edge,

the band having at least one first portion extending longitudinally having a maximum width L1, and

the band having at least one second portion having a minimum width L2, the minimum width L2 being between one third and two thirds of the maximum width L1,

wherein the first longitudinal edge is rectilinear and substantially parallel to a longitudinal axis of the band.

19. (withdrawn) The food packaging as claimed in claim 18,

wherein the lateral annular wall has a cross section which is substantially in the shape of a rectangle with rounded corners, and

wherein at least one first portion of maximum width L1 is arranged on a large side of the lateral wall of the packaging.

20. (withdrawn) A method for the production of bands intended for surrounding the periphery of a food packaging, each band extending longitudinally between two ends and having a first and a second longitudinal edge, each band having at least one first portion extending longitudinally and having a maximum width L1, and each band having at least one second portion with a minimum width L2, comprising the step of:

cutting out the first and second longitudinal edges of the bands,

wherein at least the cutting out of the second longitudinal edge is carried out by means of a device comprising at least one movable laser beam in such a way that the minimum width L2 of the bands is between one third and two thirds of the maximum width L1 and the first edge is rectilinear and substantially parallel to a longitudinal axis of the band.

21. (withdrawn) The method for the production of bands as claimed in claim 20, wherein the step of cutting out the longitudinal edges is carried out in a strip of film material

having longitudinal edges and comprising printed designs, the printed designs defining, in a direction of a width of the strip, a contour of an even number of rows of the bands arranged on the strip such that the second longitudinal edges of the bands of two successive rows are adjacent, and such that the first longitudinal edge of the band of the first row and the first longitudinal edge of the band of the last row are contiguous to the longitudinal edges of the strip,

the strip traveling with respect to the laser cutting—
out device, movements of the laser beam being synchronized with
the travel of the strip.

22. (withdrawn) A method for the production of food packagings, having a lateral annular wall extending between a bottom and an upper face, wherein the periphery of the lateral wall is surrounded by a decorative band, the band extending longitudinally between two ends and having a first and a second longitudinal edge, the band having at least one first portion extending longitudinally having maximum width L1, and the band having at least one second portion having a minimum width L2, the minimum width L2 being between one third and two thirds of the maximum width L1, the first edge being rectilinear and substantially parallel to the longitudinal axis of the band, the method comprising the steps of:

thermoforming the packagings in molds;

cutting out the longitudinal edges of the bands;

after the cutting step, delivering striplets thus

obtained as far as the molds; and

cutting out the ends of the bands, which is carried out in the vicinity of the molds.

23. (cancelled)

24. (new) The band as claimed in either claim 15, wherein the undulating line is comprised of a plurality of alternating curves.